### Pendulum saw technology reference table



Pendulum saw technology reference table	
electrical machinery	brushless motor whole
type	sealing high output
high output	0-12500/min+15%
the temperature rise of	≤25℃
the host	
noise	≤75db
host weight	1450g
output power	≥180W

work pattern	variable speed drive
disinfection mode	machine high temperature and high pressure 134(exclude battery)
charger	charger power supply voltage  AC100-240V/50-60HZ the  charger uses pulse fast  charging technology it not  only integrates foreign  advanced charging  technology and can be fully  charger within 60minutes,  and maintain the battery's  repeated service life
battery	high performance lithium ion battery Sony brand battery pack features: safe reliable and stable .voltage12V 2600mah
warranty period	18months

battery warranty period	6months
Pendulum saw	configuration
the host	1
battery	2
saw blade components	4
speed pulse charger	1
isolation channel	1
instruction book	1
qualifier acceptance certificate products	1
package	1

# Trauma hollow bone drill technology reference



Trauma hollow bone	drill technology reference
table	
electrical machinery	brushless motor hollow shaft
type	whole sealing high output
rate of revolution	$0-1250\mathrm{r/min}\pm15\%$
output torque	≥5.8N/M
the temperature rise of	<25 °C
the host	$\leq$ 25°C
noise	≤55db
the host hollow	Ø4.5mm
the host weight	1450g

output power	≥180W
work pattern	variable speed drive
radial runout	<0.1mm
disinfection mode	machine high temperature and high
distillection mode	pressure 134(exclude battery)
	charger power supply voltage
	AC100-240V/50-60HZ the charger
	uses pulse fast charging
	technology it not only integrates
charger	foreign advanced charging
	technology and can be fully
	charger within 60minutes, and
	maintain the battery's repeated
	service life
	high performance lithium ion
hottom	battery Sony brand battery pack
battery	features: safe reliable and
	stable .voltage12V 2600mah
drill chuck	hardness:HRC53 diameter:0-8mm
	(special requirements can be
	customized)
warranty period	18months

battery warranty period	6months
Trauma hollow be	one drill configuration
the host	1 set
battery	2 piece
drill chuck assembly	1 piece
drill chuck key	1 piece
speed pulse charger	1 piece
isolation channel	1 piece
instruction book	1 piece
qualifier acceptance	1 piece
certificate products	
package	1 piece

# Hollow drilling technology reference



Hollow drilling technology reference table	
electrical machinery	brushless motor whole sealing
type	high output
rate of revolution	$0-680 \mathrm{r/min} \pm 15\%$
output torque	≥8.5N/M
the temperature rise	≤25°C
of the host	≈25 C
noise	≤75db
the host hollow	Ø4.5mm
the host weight	1450g

output power	≥180W
work pattern	variable speed drive
radial runout	<0.1mm
disinfestion made	machine high temperature and high
disinfection mode	pressure 134(exclude battery)
	charger power supply voltage
	AC100-240V/50-60HZ the charger
	uses pulse fast charging
	technology it not only integrates
charger	foreign advanced charging
	technology and can be fully
	charger within 60minutes, and
	maintain the battery's repeated
	service life
battery	high performance lithium ion
	battery Sony brand battery pack
	features: safe reliable and
	stable .voltage12V 2600mah
drill chuck	hardness:HRC53
	diameter:0-8mm(sepecial
	requirements can be customized
warranty period	18months

battery warranty period	6months	
Hollow drilling configuration		
the host	1 set	
battery	2 piece	
drill chuck component	1 piece	
drill chuck key	1 piece	
speed pulse charger	1 piece	
isolation channel	1 piece	
instruction book	1 piece	
qualifier acceptance	1 .	
certificate products	1 piece	
package	1 piece	

#### Acetabular grinding drill technology reference



Acetabular grinding drill technology	
reference table	
electrical machinery type	brushless motor whole
	sealing high output
rate of revolution	$0298\text{r/min}\pm15\%$
Output torque	≥15N/M
the temperature rise of	≤25°C
the host	≈25 C
noise	≤75db
the host hollow	

the host weight	1450g
output power	≥180W
work pattern	variable speed drive
radial runout	<0.1mm
	machine high temperature and
disinfection mode	high pressure 134(exclude
	battery)
	charger power supply voltage
	AC100-240V/50-60HZ the
	charger uses pulse fast
	charging technology it not
charger	only integrates foreign
Chaigei	advanced charging technology
	and can be fully charger
	within 60minutes, and
	maintain the battery's
	repeated service life
	high performance lithium ion
battery	battery Sony brand battery
	pack features: safe reliable
	and stable .voltage12V
	2600mah

Drill chuck	hardness:HRC53	
	dianeter:0-8mm(Special	
	requirements can be	
	customized)	
warranty period	18months	
battery warranty period	6months	
Acetabular grinding drill configuration		
the host	1 set	
battery	2 piece	
drill collet assembly	1 piece	
drill collet key	1 piece	
speed pulse charger	1 piece	
isolation channel	1 piece	
instruction book	1 piece	
qualifier acceptance	1	
certificate products	1 piece	
package	1 piece	

#### Sternal saw technical reference



Sternal saw	technical reference table
electrical machinery type	brushless motor whole sealing high output
rate of revolution	$0-10000\mathrm{r/min}\pm15\%$
the temperature rise of the host	≤25°C
noise	≤75db
the host	1450g

weight	
output power	≥180W
work pattern	variable speed drive
disinfection mode	machine high temperature and high pressure 134(exclude battery)
charger	charger power supply voltage    AC100-240V/50-60HZ the    charger uses pulse fast    charging technology it not    only integrates foreign    advanced charging technology    and can be fully charger    within 60minutes, and    maintain the battery's    repeated service life
battery	high performance lithium ion battery Sony brand battery pack features: safe reliable and stable .voltage12V 2600mah

warranty period	18months
Sternum saw	accessory configuration
the host	1 set
battery	2 piece
protection	
frame	1 piece
assembly	
sternal saw	2 piece
blade	
speed pulse	1 piece
charger	
isolation	1 piece
channel	
instruction	1 piece
book	
qualifier	
acceptance	1 nioso
certificate	1 piece
products	
package	1 piece